



MIYATA



Professional Competition Racer



P-1

SPECIFICATIONS FOR MIYATA BICYCLE PROFESSIONAL MODEL P - 1

FRAME: Double butted chrome molybdenum tubing throughout, including stays and fork with forged ends. Chrome fork tips, crown and rear stays, lugs are of Italian style cut-away.

Frame size - 21", 23".

Head & seat tube angle - 72° x 72°

Head set - Microadjuster head set, Tange Model MA-60

GEAR & CRANKS: Light alloy, Shimano DUR-ACE, 1/2"x3/32"x47/52 teeth double chainwheel. Light alloy forged cotterless cranks.

WHEELS:

Tire & tubes - Soyo #90, 27" x 1-1/8" tubular, w/French pattern valves.

Rims - Light alloy tubing rim 27" x 1-1/8"

Spokes - Double butted stainless steel spoke, #15/16G.

Hubs - Shimano large flanged light alloy with quick release.

Freewheel - Shimano 14, 16, 18, 21 and 24T.

DERAILIEUR:

Front - Shimano TITLIST

Rear - Shimano CRANE

Shift lever - Shimano FINGER TIP handlebar end control.

HANDLE BAR: Nitto OLYMPIAD, light alloy.

Stem - Forged light alloy stem Nitto PEARL 90m/m (Stainless steel recessed allen head stem expander bolt).

Grips - Fujita, cotton tapes

BRAKES: Shimano TOURNEY center pull, light alloy.

SADDLE: Plastic top covered with stitched leather, Fujita SEAMLESS 17 SUPER DE-LUXE with forged light alloy seat pillar, Sakae ROYAL-P1.

CHAIN: 1/2" x 3/32" x 112 links.

PEDALS: Rat-trap type light alloy body KKT POROACE-ROAD. With toe clips and straps.

ACCESSORIES: Plastic bottle with cage, Primus frame pump Model DX-18.

WEIGHT: Approx. 22 lbs.

COLOUR




White (W18)




Black (K-8)



Blue (B88)



Gold (Y39)



Silver (W-1)

Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601

Phone. 312/641-0360. Telex. WU25-3652



MIYATA



"Where performance is better than promise"



TOP-2

SPECIFICATIONS FOR 1974 MIYATA BICYCLE PROFESSIONAL COMPETITION RACER MODEL P-2

FRAME:

Butted chrome molybdenum tubing. Chrome fork tips and rear stays with Suntour forged ends. Lugs are of Italian style cut-away.

- Top tube — 22-9/16"
- Seat tube — 21" & 23"
- Chain stay — 17-3/4"
- Head angle — 72 degrees
- Seat angle — 72 degrees
- Wheel base — 41-1/4"
- Bottom bracket height — 10-3/4"

Head set — Microadjuster head set. Tange Model MA-60.

GEAR &

CRANKS: Light alloy. Sakae CUSTOM 3 1/2" x 3/32" x 47/52 teeth double chainwheels. Light alloy melt forged cotter-less cranks. With light alloy chain cover.

WHEELS:

Tires & tubes — MYT Racer model 27" x 1-1/4" wired-on gum side wall tires and butyl tubes with American pattern valves.

Rims — Araya light alloy 27" x 1-1/4" wired-on.

Spokes — GODO stainless steel spoke, #15G.

Hubs — Shimano large flanged light alloy with quick release.

Freewheel — Shimano 14, 17, 20, 24, and 28T

DERAILLEUR:

Front — Shimano TITLIST

Rear — Shimano CRANE

Shift lever — Shimano double lever

HANDLEBAR:

Sakae CUSTOM, light alloy with light alloy stem SR-80AH (recessed bolt). And Fujita cotton tapes with plugs.

BRAKES:

Shimano, Center pull light alloy with safety lever & quick release.

SADDLE:

Fujita seamless (molded plastic top). With light alloy seat pillar, Sakae CUSTOM-P1.

CHAIN:

1/2" x 3/32" x 114 links.

PEDALS:

Rat-trap type, light alloy plate w/amber reflector, KKT Model RT-SFAL.

SPOKE


PROTECTOR: 7-1/2" c.p.

ACCESSORIES: MKS model 64-2 toe clips and MKS model 67-11 straps.

WEIGHT:

26 lbs.

COLOUR:



White (W18)



Yellow (Y27)



Copper (Y39)



Blue (B88)



Green (G59)

Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601

Phone. 312/641-0360. Telex. WU25-3652



MIYATA



DELUXE Road Racer TOURNEY



10DX-T

SPECIFICATIONS:

FRAME: Built of butted hightension steel tubing throughout #1024 Chrome fork tips and rear stays. Brazed on 5 cable stops. Lugs are of Italian style cut-away.

- Top tube — 22-9/16"
- Seat tube — 21" or 23"
- Chain stay — 17-3/4"
- Head angle — 72 degrees
- Seat angle — 72 degrees
- Wheel base — 41-3/16"
- Bottom bracket height — 10-1/2"
- Fork rake — 2-3/4"
- Head set — Microadjuster head set. Tange Model MA-60

GEAR & CRANKS: Light alloy. Takagi TOURNEY 1/2"x3/32"x40/52 teeth double chainwheels. Light alloy forged cotterless cranks. With light alloy ring type chain cover.

WHEELS:

- Tire & tube — Racer model 27"x1-1/8" wired-on, skin side tires and butyl tubes with American pattern valves
- Rims — Light alloy, 27"x1-1/4" wired-on
- Spokes — GODO, steel spoke, U/P, #14G
- Hubs — Shimano large flanged light alloy with quick release.
- Freewheel — Shimano 14, 17, 22, 28A and 34A teeth, gold finished.

DERAILLEUR:

- Front — Shimano TITLIST
- Rear — Shimano TOURNEY GS
- Shift lever — Shimano FINGER-TIP Bar end control

HANDLEBAR:

Sakae RANDONNEUR light alloy with light alloy stem Sakae SR-60E or 80E. with vinyl tape.

BRAKES:

Shimano, TOURNEY center pull light alloy with dual lever and quick release

SADDLE:

Ariake vinyl top, padded. With light alloy seat post

CHAIN:

1/2" x 3/32" x 116 links

PEDALS:

Light alloy Rat-trap type with amber C.H.P reflector, Mikashima Model K-33

SPOKE PROTECTOR:

Light alloy 8-1/2"


STAND:

Light alloy center stand

ACCESSORIES:

Tool kit & tool bag.


COLOUR:



White (W18)



Blue (B88)



Yellow (Y27)

Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601

Phone. 312/641-0360. Telex. WU25-3652

DISTRIBUTOR:



MIYATA



"Where performance is better than promise"



10DX-S

SPECIFICATIONS FOR 1974 MIYATA BICYCLE DELUXE ROAD RACER MODEL DX-S

FRAME:

Built of butted high tension steel tubing throughout. Chrome fork tips and rear stays. Brazed on 5 cable stops. Lugs are of Italian style cut-away.

- Top tube — 22-9/16"
- Seat tube — 21" & 23"
- Chain stay — 17-3/4"
- Head angle — 72 degrees
- Seat angle — 72 degrees
- Wheel base — 41-3/16"
- Bottom bracket height — 10-1/2"
- Fork rake — 2-3/4"

GEAR & CRANKS:

Light alloy. Sakae APEX 1/2" x 3/32" x 40/52 teeth double chainwheels. Light alloy forged cotter-less cranks. With ring type chain cover.

WHEELS:

- Tires & Tubes — MYT Racer model, 27" x 1-1/4" wired-on, gum side wall tires and butyl tubes with American pattern valves.
- Rims — Araya or Ukai model, 27" x 1-1/4" wired-on, c.p.
- Spokes — GODO, steel spoke, U/P, #15G.
- Hubs — Shimano large flanged light alloy with quick release.
- Freewheel — Shimano 14, 17, 22, 27 and 32T.

DERAILLEUR:

- Front — Shimano TITLIST
- Rear — Shimano TOURNEY GS
- Shift lever — Shimano double lever

HANDLEBAR:

Sakae CUSTOM light alloy with light alloy stem Sakae SR-80. And vinyl tape with plugs.

BRAKES:

Shimano, center pull light alloy with dual lever and quick release.

SADDLE:

Ariake, vinyl top, padded. With light alloy seat post.

CHAIN:

1/2" x 3/32" x 114 links.


PEDALS:

Rat-trap type with amber reflector, KKT Model RT-SF.

SPOKE

- PROTECTOR: 8-1/2" c.p.
- REFLECTOR: 2" diam., SAE class A.
- STAND: Light alloy center stand.
- WEIGHT: 30 lbs.

COLOUR




Pearl White (W18)



Yellow (Y27)



Copper (Y39)



Blue (B88)



Green (G59)

Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601

Phone. 312/641-0360. Telex. WU25-3652

SOLD AND SERVICED BY



MIYATA



DELUXE Road Racer



STD-A

SPECIFICATIONS FOR 1974-5 MIYATA BICYCLE SPORTS MODEL STD-A

FRAME: Built of best quality steel tubing. Brazed on 5 cable stops. Fully lugged frame. Chrome fork tips.

Frame size — Men's 21", 23", 25".

Head & seat angle — 72° x 72°

Bottom bracket height — 10½"

Head set — Nikyo Model 65-4

GEAR & CRANKS: Takagi TOURNEY forged light alloy cotterless cranks and light alloy chainwheel, 1/2"x3/32"x52/40 teeth 5 pins double chainwheels with light alloy chain guard.

Tires & tubes — 27" x 1-1/4" wired-on gumwall tires and butyl tube with American pattern valves.

Rims — Light alloy rims, 27" x 1-1/4" wired-on

Hubs — Shimano light alloy large flanged hubs with quick release for front & rear.

Spokes — #14G, u.c.p.

Freewheel — Suntour 14-28 teeth.

DERAILLEURS:

Front — Suntour SPIRT

Rear — Suntour GT

Shift lever — Suntour power shifter at handle bar stem
PUB-10

HANDLE: Sakae light alloy Randonneur type with light alloy stem (21" — SR60E. 23" — SR80E. 25" — SR100E).

BRAKES: DIA-COMPE Center pull light alloy brake with quick release w/safety lever.

CHAIN: 1/2" x 3/32" x 114 links

PEDALS: Rat trap type with Amber C.H.P. reflector, Mikashima Model 33.

SADDLE: Ariake, vinyl top, plastic base padded.

BAR TAPE: Vinyl tape w/plugs, tape on.

STAND: Center kick stand, steel.

SPOKE PROTECTOR: 7-1/2" c.p.

TOOLS: 7 way spanner

COLOUR:



White (W18)



Blue (B88)



Yellow (Y27)

Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601

Phone. 312/641-0360. Telex. WU25-3652

DISTRIBUTOR:



MIYATA



Racer, 10 Speed model



SPECIFICATIONS FOR 1974-5 MIYATA BICYCLE SPORTS MODEL S-1

FRAME: Built of best quality steel tubing. Brazed on 4-5 cable stops.

- Frame size — Men's 19-1/2", 21", 23".
- Head & seat angle — 71 degrees x 71 degrees
- Head set — 65-4

CEAR & CRANKS: Steel double chainwheels, 1/2" x 3/32" x 40/52 teeth. With ring type chain cover.

WHEELS:

- Tyre & tube — MYT Racer model, 27" x 1-1/4" wired-on gumside wall tires and butyl tubes. With American pattern valves.
- Spokes — #14G steel, u.c.p.
- Rims — 27" x 1-1/4" steel c.p. wired-on.
- Hubs — Semi-large flanged hubs, steel c.p.
- Freewheel — Suntour PERFECT 14-28 teeth.



DERAILLEURS:

- Front — Suntour SPIRT
- Rear — Suntour HONOR
- Shift lever — Suntour UB-10 at handlebar stem.

HANDLEBAR: Sakae steel c.p. racing style handlebar with light alloy stem JUN-50.

- GRIPS: — Vinyl tape with plugs, tape on.
- BRANKES: — DIA-COMPE center pull light alloy brake with safety lever.
- SADDLE: — Ariake racing type padded saddle.
- CHAIN: — 1/2" x 3/32" x 114 links
- PEDALS: — Rat-trap with amber reflectors.
- SPOKE PROTECTOR: — 7-1/2" c.p.
- STAND: — Center kick stand, steel.

COLOUR:



Imported by

TOYODA AMERICA INC.

221 North La Salle Street, Chicago, Illinois 60601
Phone. 312/641-0360. Telex. WU25-3652

DISTRIBUTOR: